



Evolution Wireless Digital EW-DP SKP | Digital plug-on transmitter



Digital UHF XLR plug-on transmitter featuring +48V phantom power, microSD card slot, and 3.5 mm lav mic input for use with Evolution Wireless Digital.

FEATURES

- Fully digital UHF wireless microphone system for video applications
- Integrated Bluetooth for synchronization and control
- Smart Notifications for troubleshooting and system guidance
- Intelligent battery management provides operating time (hours:minutes)
- Extended battery life: up to 12h on transmitter, 7h on receiver (SKP up to 6h)
- Magnetically stackable components for versatile mounting
- Industry leading 134 dB dynamic range for distortion free transmission
- Up to 56 MHz bandwidth for flexibility in any RF environment
- Exceptionally low latency (1.9 ms)
- External charging and powering via USB-C (receiver only)
- Smart Assist app for monitor & control
- Optional plug-on transmitter features XLR & 3.5 mm inputs, +48V & recording via microSD (ENG Set or component only)

DELIVERY INCLUDES

- EW-DP SKP digital plug-on transmitter
- 2 AA batteries



Evolution Wireless Digital

EW-DP SKP | Digital plug-on transmitter

SPECIFICATIONS

System		EW-DP SKP
Audio link frequency ranges	Q1-6	470.2 - 526 MHz
	R1-6	520 - 576 MHz
	R4-9	552 - 607.8 MHz
	S1-7	606.2 - 662 MHz
	S4-7	630 - 662 MHz
	S7-10	662 - 693.8 MHz
	U1/5	823.2 - 831.8 MHz & 863.2 - 864.8 MHz
	V3-4	925.2 - 937.3 MHz
	Y1-3	1785.2 - 1799.8 MHz
Bluetooth® Low Energy (BLE) frequency range	2402 - 2480 MHz	
Audio frequency response	20 Hz - 20 kHz (-3 dB) @ 3 dBfs	
Audio THD	≤ -60 dB for 1 kHz @ -3 dBfs input level	
Dynamic range	134 dB	
System latency	1.9 ms	
Operating temperature	-10 °C - +55 °C (14 °F - 131 °F)	
Relative humidity	5 - 95 % (non-condensing)	
Input voltage		~ 2.0 - 4.35 V
Input current		< 300 mA / (without record and P48)
Power Supply		2x AA batteries 1.5V or BA70 rechargeable battery pack
Transmit power		Audio link: 10 mW ERP BLE: max. 10 mW EIRP
Audio output power		< 2 dBV max. (high level) / < 4dBU max (high level)
Output power XLR		max. 10 mA
Dimensions		108 x 42 mm
Weight (without batteries)		ca. 163 g (0.36 lbs)

PRODUCT VARIANTS

EW-DP SKP (Q1-6)	470.2 - 526 MHz	Art. no. 700080
EW-DP SKP (R1-6)	520 - 576 MHz	Art. no. 700081
EW-DP SKP (R4-9)	552 - 607.8 MHz	Art. no. 700082
EW-DP SKP (S1-7)	606.2 - 662 MHz	Art. no. 700083
EW-DP SKP (S4-7)	630 - 662 MHz	Art. no. 700084
EW-DP SKP (S7-10)	662 - 693.8 MHz	Art. no. 700085
EW-DP SKP (U1/5)	823.2 - 831.8 MHz & 863.2 - 864.8 MHz	Art. no. 700086
EW-DP SKP (V3-4)	925.2 - 937.3 MHz	Art. no. 700088
EW-DP SKP (Y1-3)	1785.2 - 1799.8 MHz	Art. no. 700089

ACCESSORIES

Mounting Plate Set	Mounting kit for EW-DP (Mounting plate, mounting screws, cold shoe mount, allen key, and belt clip)	Art. no. 700005
Mounting Plate	Single mounting plate	Art. no. 588188
CL35	3.5 mm to 3.5 mm TRS coiled cable	Art. no. 586365
CL35-Y	3.5 mm to dual-3.5 mm TRS coiled cable	Art. no. 700061
CL35XLR	3.5 mm to XLR plug coiled cable	Art. no. 700062
BA 70	Rechargeable battery pack for SK,SKM-S, SKP	Art. no. 508860
L 70 USB	Charger for BA 70 rechargeable battery pack	Art. no. 508861
EW-D CHARGING SET	Set of L 70 USB charger and 2 BA 70 rechargeable battery packs	Art. no. 508862



Evolution Wireless Digital

EW-DP SKP | Digital plug-on transmitter

DIMENSIONS

EW-DP SKP

