

## MOT 500 A MULTICAST COMPACT

The digital TV modulator **MOT 500 A MULTICAST COMPACT** can be used as an analog and digital transmitter. This device has an analog output power of 500W ps, a digital output power of 300W rms in DVB-T/T2 and ISDBT, and 400W rms in ATSC. It can be configured with different input interfaces and it is suitable for DVB-T/H, DVB-T2, ISDB-T/TB and ATSC standards, in addition of PAL and NTSC on its analog version. It includes adaptive pre-correction and a high precision GPS receiver for SFN networks.



### MAIN ADVANTAGES

- High efficiency wideband amplifiers technology.
- Compatible with PAL, NTSC, DVB-T/H, DVB-T2, ISDB-T/TB, ATSC and ATSC 3.0 modulations.
- Multiple modulations available and selectable for the user.
- With Re-Multiplexer/BTS Adapter and Layer Combiner for ISDB-TB.
- Lineal, non-lineal and adaptive pre-correction.
- On-board high stability GPS receiver.
- Flexible input interfaces.
- MFN and SFN modes.
- SNMP, web interface and LC display indicator.

### GENERAL CHARACTERISTICS

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| <b>ANALOG OUTPUT POWER</b>       | 500W ps                                   |
| <b>DIGITAL OUTPUT POWER</b>      | 300W rms                                  |
| <b>DVB-T/T2, ISDBT-TB</b>        |                                           |
| <b>DIGITAL OUTPUT POWER ATSC</b> | 400W rms                                  |
| <b>MER</b>                       | >36dB for any output power                |
| <b>FREQUENCY AGILITY</b>         | Bands IV-V                                |
| <b>FREQUENCY STABILITY</b>       | 2*10-8@10MHz long period                  |
| <b>RF OUTPUT CONNECTOR</b>       | 7/16"(F), 50 Ohm                          |
| <b>POWER SUPPLY</b>              | Single phase 100-240V, 50/60Hz            |
| <b>AVERAGE CONSUMPTION</b>       | 1300VA                                    |
| <b>DIMENSIONS</b>                | Three standard rack units of 19"          |
| <b>CONTROL</b>                   | Front panel, web interface, SNMP and GPIO |
| <b>OPERATING TEMPERATURE</b>     | -5 to +45°C                               |
| <b>MAXIMUM RELATIVE HUMIDITY</b> | 95% without condensation                  |
| <b>APPROXIMATE WEIGHT</b>        | 24Kg                                      |

## MODULATOR

| <b>DVB-T/-H/-T2</b>            |                                                                                                                                             |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>STANDARD</b>                | EN300744, EN302304, EN302755, TS101191, TS102773 (T2-MI), TS102034                                                                          |
| <b>INPUTS</b>                  | 4xASI BNC(F), 75 Ohm & 2xRJ45 TSolP GBE<br>Switch seamless between ASI inputs.<br>Hierarchical and not hierarchical (DVB-T)                 |
| <b>FFT</b>                     | 1K (DVB-T2), 2K, 4K, 8K, 8K ext. (DVB-T2), 16K & 16K ext. (DVB-T2), 32K & 32K ext. (DVB-T2)                                                 |
| <b>CODE RATE</b>               | All modalities available according to the standard<br>Block Short or Normal (DVB-T2)<br>DVB-T: Reed-Solomon (204, 188)<br>DVB-T2: BCH, LDPC |
| <b>GUARD INTERVAL</b>          | 1/32, 1/16, 1/8, 1/4, 19/256 (DVB-T2), 19/128 (DVB-T2), 1/128 (DVB-T2)                                                                      |
| <b>CONSTELLATION</b>           | QPSK, 16QAM, 64QAM, 256QAM (DVB-T2).<br>Rotated and non rotated (DVB-T2)                                                                    |
| <b>MISO PROCESSING</b>         | Supported                                                                                                                                   |
| <b>ISDB-TB</b>                 |                                                                                                                                             |
| <b>STANDARD</b>                | ABNT NBR 15601, ABNT NBR 15603                                                                                                              |
| <b>INPUTS</b>                  | 4xASI TS/BTS BNC (F), 75 Ohm & 2xRJ45 TS/BTSolP GBE                                                                                         |
| <b>FFT</b>                     | Mode 1 (2K), Mode 2 (4K), Mode 3 (8K)                                                                                                       |
| <b>CODE RATE</b>               | 1/2, 2/3, 3/4, 5/6, 7/8                                                                                                                     |
| <b>GUARD INTERVAL</b>          | 1/4, 1/8, 1/16, 1/32                                                                                                                        |
| <b>HIERARCHICAL MODULATION</b> | Up to three layers                                                                                                                          |
| <b>CONSTELLATION</b>           | QPSK, 16QAM, 64QAM                                                                                                                          |
| <b>TIME INTERLEAVER</b>        | Supported                                                                                                                                   |
| <b>PARTIAL RECEPTION</b>       | Supported                                                                                                                                   |
| <b>ATSC</b>                    |                                                                                                                                             |
| <b>STANDARD</b>                | A/53, A/110                                                                                                                                 |
| <b>INPUTS</b>                  | 4xASI/SMPTE-310M BNC(H), 75Ohm & 2xRJ45 TSolP GBE                                                                                           |
| <b>MODULATION</b>              | 8-VSB                                                                                                                                       |
| <b>INPUT BIT RATE</b>          | 19.39 Mbit/s                                                                                                                                |
| <b>BANDWIDTH</b>               | 6MHz                                                                                                                                        |
| <b>MAX PROCESSING DELAY</b>    | Up to 1 second (programmable)                                                                                                               |

broadcast your \_ world

| <b>ANALOG</b>                  |                                                 |
|--------------------------------|-------------------------------------------------|
| <b>TV REGULATION</b>           | B, G, D, K, M, N, I1                            |
| <b>VIDEO INPUTS</b>            | CVBS, 4xSDI BNC(F), 75 Ohm                      |
| <b>AUDIO INPUTS</b>            | Balanced audio 600 Ohm mini XLR(M), SDI embebed |
| <b>COLOUR STANDARDS</b>        | PAL, NTSC                                       |
| <b>AUDIO STANDARDS</b>         | IRT dual sound, FM (-10dB)                      |
| <b>VIDEO INPUT</b>             | 0.5-1.5V                                        |
| <b>DIFFERENTIAL GAIN</b>       | ±3%                                             |
| <b>DIFFERENTIAL PHASE</b>      | ±3°                                             |
| <b>LOW FREQUENCY LINEARITY</b> | 8%                                              |
| <b>ICPM</b>                    | ±2"                                             |
| <b>S/N</b>                     | >60dB                                           |
| <b>K FACTOR</b>                | 2%                                              |
| <b>20T</b>                     | 3%                                              |
| <b>SPURIOUS AND HARMONICS</b>  | >60dB                                           |
| <b>CHANNEL INTERMODULATION</b> | >58dB                                           |
| <b>MODULATION CAPABILITY</b>   | ±120KHz                                         |
| <b>MONAURAL INPUT</b>          | Programmable 0-12dBm                            |
| <b>PRE-EMPHASIS</b>            | 50/70µs                                         |
| <b>FREQUENCY RESPONSE</b>      | ±0.5dB from 30Hz-15KHz                          |
| <b>HARMONIC DISTORTION</b>     | 0.5% from 30Hz-15KHz                            |
| <b>AM NOISE</b>                | 50dB from 30Hz-15KHz                            |
| <b>FM NOISE</b>                | 60dB with de-emphasis                           |
| <b>SYNCHRONOUS AM NOISE</b>    | >50dB                                           |

## GPS

|                                     |                                                 |
|-------------------------------------|-------------------------------------------------|
| <b>INPUT CONNECTOR</b>              | TNC(F), 50 Ohm                                  |
| <b>INPUT/OUTPUT REFERENCE 10MHz</b> | BNC(F), 75 Ohm                                  |
| <b>INPUT/OUTPUT REFERENCE 1PPS</b>  | BNC(F), 75 Ohm                                  |
| <b>HOLD-OVER STABILITY</b>          | 5µs after 5 hours (optional 1µs after 24 hours) |

NOTE: These transmitters have to be operated with suitable filters at the RF output, so as to meet the standards and limits for the suppression of out of band emissions.

*\* The images and/or technical specifications are subject to change without previous notice.*

broadcast your \_ world